(0.063-inch) thickness (such as steel strapping or paperboard) can be passed between the bottom of the IBC and the platform. Other methods at least equally effective may be used (see §178.801(i))

(c) Criteria for passing the test. An IBC passes the vibration test if there is no rupture or leakage.

[Amdt. 178–103, 59 FR 38074, July 26, 1994, as amended by Amdt. 178-108, 60 FR 40038, Aug. 4, 1995; Amdt. 178-110, 60 FR 49111, Sept. 21, 1995; 66 FR 45386, Aug. 28, 2001; 75 FR 5397, Feb. 2, 2010]

Subpart P—Large Packagings **Standards**

SOURCE: 75 FR 5397, Feb. 2, 2010, unless otherwise noted.

§178.900 Purpose and scope.

- (a) This subpart prescribes requirements for Large Packaging intended for the transportation of hazardous materials. Standards for these packagings are based on the UN Recommendations.
- (b) Terms used in this subpart are defined in §171.8 of this subchapter.

§178.905 Large Packaging identification codes.

Large packaging code designations consist of: two numerals specified in paragraph (a) of this section; followed by the capital letter(s) specified in paragraph (b) of this section.

(a) Large packaging code number designations are as follows: 50 for rigid Large Packagings; or 51 for flexible Large Packagings.

(b) Large Packagings code letter des-

ignations are as follows:
(1) "A" means steel (all types and surface treatments).

(2) "B" means aluminum.(3) "C" means natural wood.

(4) "D" means plywood.

(5) "F" means reconstituted wood. (6) "G" means fiberboard.

(7) "H" means plastic.

(8) "M" means paper, multiwall.

(9) "N" means metal (other than steel or aluminum).

§178.910 Marking of Large Packagings.

(a) The manufacturer must:

- (1) Mark every Large Packaging in a durable and clearly visible manner. The marking may be applied in a single line or in multiple lines provided the correct sequence is followed with the information required by this section. The following information is required in the sequence presented:
- Except as provided §178.503(e)(1)(ii), the United Nations packaging symbol as illustrated in §178.503(e)(1)(i). For metal Large Packagings on which the marking is stamped or embossed, the capital letters "UN" may be applied instead of the symbol;
- (ii) The code number designating the Large Packaging design type according to \$178.905. The letter "W" must follow the Large Packaging design type identification code on a Large Packaging when the Large Packaging differs from the requirements in subpart P of this part, or is tested using methods other than those specified in this subpart, and is approved by the Associate Administrator in accordance with the provisions in §178.955:
- (iii) A capital letter identifying the performance standard under which the design type has been successfully tested, as follows:
- (A) X—for Large Packagings meeting Packing Groups I, II and III tests;
- (B) Y-for Large Packagings meeting Packing Groups II and III tests; and
- (C) Z-for Large Packagings meeting Packing Group III test.
- (iv) The month (designated numerically) and year (last two digits) of manufacture;
- (v) The country authorizing the allocation of the mark. The letters "USA" indicate that the Large Packaging is manufactured and marked in the United States in compliance with the provisions of this subchapter.
- (vi) The name and address or symbol of the manufacturer or the approval agency certifying compliance with subpart P and subpart Q of this part. Symbols, if used, must be registered with the Associate Administrator.
- (vii) The stacking test load in kilograms (kg). For Large Packagings not designed for stacking the figure "0" must be shown.